



Faresin FS Compact 7.32 Telehandler

[Read More](#)

SKU:

Price:

Stock: instock

Categories: [All Equipment](#), [Faresin Telehandlers](#)

Tags: [faresin](#), [telehandler](#)

Product Description

<https://youtu.be/51y88HgPJrg?si=hTcisC8v4IE9p2mO>

The new FS Compact series includes 6,400 lbs maximum lifting capacity telehandlers with a maximum reachable height of 29.5 ft. Compact sizes ensure great performance boasting unique agility, impressive stability and exclusive versatility. The series is also available with a lowered cab to keep the height down to 6.8 ft.

Design

The new design combines emotion, style and technical features in every detail. The clean and essential lines are the result of experience acquired across all sectors from thousands of clients, and the meticulous work of our engineers and designers. The result is exceptional visibility for the driver.

- Lowered hood
- High-strength fenders
- High Visibility Full Led Lighting
- Wide, reclinable rearview mirrors

Cabin - 360° visibility

An ultra-technological dashboard with intuitively arranged controls, grouped in accordance with a functional logic. With regard to safety, the Rops and Fops European certification and Ansi certification for the United States are perfectly valid, in strict compliance with current legislation.

- Immediate control of all operating and safety parameters
- Highly sensitive and accurate boom controls
- Setting & programming of advanced machine management functions
- Air suspension seat with multi-regulation to reduce fatigue

Power - Plumbing

The hydraulic component is the real strength of this telehandler. Faresin Industries sought to oversize it to guarantee versatility of use, rapid work cycles, and fluid and precise movements. The hydraulic oil circuit

adopts the same design logic to provide modular solutions for all uses, always with a view to optimising performance and minimising fuel consumption.

- Flow sharing distributor with proportional hydraulic/electric control
- Ecofast valve: fluidifies and speeds up boom movements, even at low speed (PERFORMANCE and EXCELLENCE)
- Ecofast-E adds more electronic load compensation and more job security
- Electro-proportional spool and auxiliary services

Transmissions - Dedicated

All versions of the FS Compact are supplied standard with Ecodrive hydrostatic transmission control, an advanced solution able to dose the distributed power depending on the driving mode in order to best exploit the engine power while simultaneously and substantially reducing fuel consumption.

- 4-wheel drive steering with 3 steering modes
- Single gear hydrostatic transmission from 0 to 30 km/h (CLASSIC and DYNAMIC)
- Two-speed mechanical transmission with maximum speed 24.8 mph (PERFORMANCE and EXCELLENCE)
- Ecodrive: improved use of engine power to reduce fuel consumption without compromising on performance

Engine - Performance first

The longitudinal layout of the Diesel engine and connected components allow improved power transmission and efficient management of the cooling system. The integrated exchanger, positioned horizontally far from sludge and dirt, integrates an electronically controlled ventilation system that only works when needed, and which can invert the air flow to expel the accumulation of any crushed leaf dust.

- DOC+DPF and SCR exhaust gas aftertreatment (75/100 kW)
- Autonomous and reversible cooling fan
- “AutoStop”, which shuts down the engine when the operator gets up from the seat, and then turns on again

Low Cab

Faresin Industries sought to respond to market needs, adding to the standard version with a Low Cab version with maximum height of just 2,06 m at the highest point of the cab. This version is the ideal machine for a large number of applications, for example in narrow buildings with low ceilings, poultry farming, etc

- Reduced height up to 2060 mm
- Performance on par with other models

7.32c COMPACT

Main Features

- Maximum capacity 3,2 ton
- Maximum lifting height 7,1 m
- Horizontal outreach 3,6 m
- Swinging angle 155°
- Number of extracting sections 1
- Weight 6600 kg

Dimensions

- Height 2250 mm
- Height with Low Cab 2060 mm
- Width 2100 mm
- Length 4670 mm

[Download Information](#)

9.32C COMPACT

Main Features

- Maximum capacity 3,2 ton
- Maximum lifting height 9 m
- Horizontal outreach 5,9 m
- Swinging angle 155°
- Number of extracting sections 2
- Weight 6900 kg

Dimensions

- Height 2250 mm
- Height with Low Cab 2060 mm
- Width 2100 mm
- Length 4670 mm

[Download Information](#)

Choose configuration

	CLASSIC 55	CLASSIC 75	DYNAMIC 85	PERFORMANCE 85	EXCELLENCE 85
Engine	Deutz Stage V	Deutz Stage V	Deutz Stage V	Deutz Stage V	Deutz Stage V
Power	55.4 / 75 kW/hp	75 / 102 kW/hp	85 / 115 kW/hp	85 / 115 kW/hp	85 / 115 kW/hp
Aftertreatment system	DOC + DPF	DOC + DPF + SCR	DOC + DPF + SCR	DOC + DPF + SCR	DOC + DPF + SCR

	CLASSIC 55	CLASSIC 75	DYNAMIC 85	PERFORMANCE 85	EXCELLENCE 85
Hydrostatic transmission	single gear	single gear	single gear	2 mechanical gears	2 mechanical gears
Hydraulic power supply	gears pump	gears pump	gears pump	LS piston pump	LS piston pump
Hydraulic capacity flow-rate	100 l/min @ 250 bar	100 l/min @ 250 bar	120 l/min @ 250bar	150 l/min @ 250bar	150 l/min @ 250bar
Steering radius	3,8 m	3,8 m	3,8 m	3,8 m	3,8 m
Speed	30 km/h	30 km/h	30 km/h	40 km/h	40 km/h
Tyres	400/70 – 20	400/70 – 20	400/70 – 20	405/70 – 24	405/70 – 24



Faresin Compact 6.26 Classic Telehandler

[Read More](#)

SKU:

Price:

Stock: instock

Categories: [Faresin Telehandlers](#)

Tags: [faresin](#), [telehandler](#)

Product Description

[embed]https://youtu.be/WFTX-00iE4g?si=lp8HrFUJLPOosYpB[/embed]

The 6.26 Classic 52 telescopic handler from the Small Range is the right model for all situations where facilities and work environments have limited space. Its small size makes this telescopic handler an all-rounder even in tight spaces, providing excellent performance in all conditions in both agriculture and construction.

Everything under control

The driver’s cab of a telehandler is the operator’s workstation for many hours throughout the day. This is why Faresin is committed to designing and developing solutions that are always improving in terms of comfort and safety (ROPS and FOPS compliant cabin).

- Cabin among the largest on the market
- Ergonomics and visibility
- 360-degree view, always
- Efficient heating and ventilation
- Spacious and comfortable interior spaces
- Color display dashboard with built-in diagnostics
- Guaranteed security

Plumbing

Guaranteed excellent performance combined with maximum reliability.

- Distributor with mechanical/electro-proportional control
- Dual-roller joystick with integrated FNR
- Electro-proportional spool and auxiliary services

Transmission

State-of-the-art hydrostatic transmissions that provide sensitivity and power in machine travel.

- 4-wheel drive steering with 3 steering modes
- Single gear with reversing horn
- Maximum speed 30 km/h
- CREEPER mode optional

Engines

Faresin has equipped its telehandlers with new 51.7 kW Stage V-compliant engines capable of ensuring excellent performance combined with low fuel consumption. Equipped with exhaust gas after-treatment system with DOC+DPF they result efficient and environmentally friendly. They do not require the use of Urea/AdBlue thus allowing operating costs to be kept low.

- Accessible engine compartment for easy maintenance
- Exhaust gas post treatment with DOC+DPF
- Increased radiant surface area
- Clean and efficient

6.26 CLASSIC 52

Main Features

- Maximum capacity 2,6 ton
- Max lifting height 5,9 m
- Horizontal boom extension 3,2 m
- Swinging angle 155°
- Number of extracting sections 1
- Weight 4700 kg
- Speed 30 km/h

Configuration

- Yanmar 51.7 / 69.3 kW/hp engine
- Aftertreatment system DOC + DPF
- Hydrostatic transmission single gear
- Hydraulic gear pump power supply
- Hydraulic capacity flow rate 80 l/min @ 230 bar
- Turning radius 3.25 m
- Wheels 12-16.5

Dimensions

- Height 1935 mm
- Width 1890 mm
- Length 4035 mm

[Download Information](#)
