



Faresin Compact 6.26 Classic Telehandler

[Read More](#)

SKU:

Price:

Stock: instock

Categories: [Faresin Telehandlers](#)

Tags: [faresin](#), [telehandler](#)

Product Description

[embed]https://youtu.be/WFTX-00iE4g?si=lp8HrFUJLPOosYpB[/embed]

The 6.26 Classic 52 telescopic handler from the Small Range is the right model for all situations where facilities and work environments have limited space. Its small size makes this telescopic handler an all-rounder even in tight spaces, providing excellent performance in all conditions in both agriculture and construction.

Everything under control

The driver's cab of a telehandler is the operator's workstation for many hours throughout the day. This is why Faresin is committed to designing and developing solutions that are always improving in terms of comfort and safety (ROPS and FOPS compliant cabin).

- Cabin among the largest on the market
- Ergonomics and visibility
- 360-degree view, always
- Efficient heating and ventilation
- Spacious and comfortable interior spaces
- Color display dashboard with built-in diagnostics
- Guaranteed security

Plumbing

Guaranteed excellent performance combined with maximum reliability.

- Distributor with mechanical/electro-proportional control
- Dual-roller joystick with integrated FNR
- Electro-proportional spool and auxiliary services

Transmission

State-of-the-art hydrostatic transmissions that provide sensitivity and power in machine travel.

- 4-wheel drive steering with 3 steering modes
- Single gear with reversing horn
- Maximum speed 30 km/h
- CREEPER mode optional

Engines

Faresin has equipped its telehandlers with new 51.7 kW Stage V-compliant engines capable of ensuring excellent performance combined with low fuel consumption. Equipped with exhaust gas after-treatment system with DOC+DPF they result efficient and environmentally friendly. They do not require the use of Urea/AdBlue thus allowing operating costs to be kept low.

- Accessible engine compartment for easy maintenance
- Exhaust gas post treatment with DOC+DPF
- Increased radiant surface area
- Clean and efficient

6.26 CLASSIC 52

Main Features

- Maximum capacity 2,6 ton
- Max lifting height 5,9 m
- Horizontal boom extension 3,2 m
- Swinging angle 155°
- Number of extracting sections 1
- Weight 4700 kg
- Speed 30 km/h

Configuration

- Yanmar 51.7 / 69.3 kW/hp engine
- Aftertreatment system DOC + DPF
- Hydrostatic transmission single gear
- Hydraulic gear pump power supply
- Hydraulic capacity flow rate 80 l/min @ 230 bar
- Turning radius 3.25 m
- Wheels 12-16.5

Dimensions

- Height 1935 mm
- Width 1890 mm
- Length 4035 mm

[Download Information](#)
