



## Faresin FS Compact 7.32 Telehandler

[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Faresin Telehandlers](#), [All Equipment](#)

**Tags:** [faresin](#), [telehandler](#)

### Product Description

<https://youtu.be/51y88HgPJrg?si=hTcisC8v4IE9p2mO>

The new FS Compact series includes 6,400 lbs maximum lifting capacity telehandlers with a maximum reachable height of 29.5 ft. Compact sizes ensure great performance boasting unique agility, impressive stability and exclusive versatility. The series is also available with a lowered cab to keep the height down to 6.8 ft.

### Design

The new design combines emotion, style and technical features in every detail. The clean and essential lines are the result of experience acquired across all sectors from thousands of clients, and the meticulous work of our engineers and designers. The result is exceptional visibility for the driver.

- Lowered hood
- High-strength fenders
- High Visibility Full Led Lighting
- Wide, reclinable rearview mirrors

### Cabin - 360° visibility

An ultra-technological dashboard with intuitively arranged controls, grouped in accordance with a functional logic. With regard to safety, the Rops and Fops European certification and Ansi certification for the United States are perfectly valid, in strict compliance with current legislation.

- Immediate control of all operating and safety parameters
- Highly sensitive and accurate boom controls
- Setting & programming of advanced machine management functions
- Air suspension seat with multi-regulation to reduce fatigue

### Power - Plumbing

The hydraulic component is the real strength of this telehandler. Faresin Industries sought to oversize it to guarantee versatility of use, rapid work cycles, and fluid and precise movements. The hydraulic oil circuit

adopts the same design logic to provide modular solutions for all uses, always with a view to optimising performance and minimising fuel consumption.

- Flow sharing distributor with proportional hydraulic/electric control
- Ecofast valve: fluidifies and speeds up boom movements, even at low speed (PERFORMANCE and EXCELLENCE)
- Ecofast-E adds more electronic load compensation and more job security
- Electro-proportional spool and auxiliary services

## Transmissions - Dedicated

All versions of the FS Compact are supplied standard with Ecodrive hydrostatic transmission control, an advanced solution able to dose the distributed power depending on the driving mode in order to best exploit the engine power while simultaneously and substantially reducing fuel consumption.

- 4-wheel drive steering with 3 steering modes
- Single gear hydrostatic transmission from 0 to 30 km/h (CLASSIC and DYNAMIC)
- Two-speed mechanical transmission with maximum speed 24.8 mph (PERFORMANCE and EXCELLENCE)
- Ecodrive: improved use of engine power to reduce fuel consumption without compromising on performance

## Engine - Performance first

The longitudinal layout of the Diesel engine and connected components allow improved power transmission and efficient management of the cooling system. The integrated exchanger, positioned horizontally far from sludge and dirt, integrates an electronically controlled ventilation system that only works when needed, and which can invert the air flow to expel the accumulation of any crushed leaf dust.

- DOC+DPF and SCR exhaust gas aftertreatment (75/100 kW)
- Autonomous and reversible cooling fan
- “AutoStop”, which shuts down the engine when the operator gets up from the seat, and then turns on again

## Low Cab

Faresin Industries sought to respond to market needs, adding to the standard version with a Low Cab version with maximum height of just 2,06 m at the highest point of the cab. This version is the ideal machine for a large number of applications, for example in narrow buildings with low ceilings, poultry farming, etc

- Reduced height up to 2060 mm
- Performance on par with other models

## 7.32c COMPACT

Main Features

- Maximum capacity 3,2 ton
- Maximum lifting height 7,1 m
- Horizontal outreach 3,6 m
- Swinging angle 155°
- Number of extracting sections 1
- Weight 6600 kg

Dimensions

- Height 2250 mm
- Height with Low Cab 2060 mm
- Width 2100 mm
- Length 4670 mm

[Download Information](#)

9.32C COMPACT

Main Features

- Maximum capacity 3,2 ton
- Maximum lifting height 9 m
- Horizontal outreach 5,9 m
- Swinging angle 155°
- Number of extracting sections 2
- Weight 6900 kg

Dimensions

- Height 2250 mm
- Height with Low Cab 2060 mm
- Width 2100 mm
- Length 4670 mm

[Download Information](#)

Choose configuration

	CLASSIC 55	CLASSIC 75	DYNAMIC 85	PERFORMANCE 85	EXCELLENCE 85
Engine	Deutz Stage V	Deutz Stage V	Deutz Stage V	Deutz Stage V	Deutz Stage V
Power	55.4 / 75 kW/hp	75 / 102 kW/hp	85 / 115 kW/hp	85 / 115 kW/hp	85 / 115 kW/hp
Aftertreatment system	DOC + DPF	DOC + DPF + SCR	DOC + DPF + SCR	DOC + DPF + SCR	DOC + DPF + SCR

	CLASSIC 55	CLASSIC 75	DYNAMIC 85	PERFORMANCE 85	EXCELLENCE 85
Hydrostatic transmission	single gear	single gear	single gear	2 mechanical gears	2 mechanical gears
Hydraulic power supply	gears pump	gears pump	gears pump	LS piston pump	LS piston pump
Hydraulic capacity flow-rate	100 l/min @ 250 bar	100 l/min @ 250 bar	120 l/min @ 250bar	150 l/min @ 250bar	150 l/min @ 250bar
Steering radius	3,8 m	3,8 m	3,8 m	3,8 m	3,8 m
Speed	30 km/h	30 km/h	30 km/h	40 km/h	40 km/h
Tyres	400/70 – 20	400/70 – 20	400/70 – 20	405/70 – 24	405/70 – 24