

Supreme 700T Twin Auger

Read More

SKU:

Price:

Stock: instock

Categories: All Equipment, Supreme TMR Feed Mixer Wagons

Tags: mixer, supreme

Product Description

[embed]https://youtu.be/_oFsvTe1ju8?si=rinIhehWo7ED7uNa[/embed] A Supreme Feed Processor helps you provide nutritious rations for your cattle by improved mix quality through superior tub and auger design. Along with great ROI from your feedstuffs, a Supreme Feed Processor provides a great investment as it holds high resale value. You enjoy the reliability you need from a well-built machine made with quality components. The 700T Pull-Type has a maximum payload of 14,000 lbs (6,350 kg), struck capacity of 565 ft^3 (16.0 m^3) or 649 ft^3 (18.4 m^3) with tub extension, and requires 100 horse power (75 kW). Unlike most other vertical mixers that use smaller single stage planetary drives, Supreme uses the heaviest two-stage planetary drive available. Combined with a heavy duty gearbox, this robust system rotates the auger through the toughest of materials. This simple design features few moving parts with no chains, sprockets or countershafts to worry about. Each Supreme pull type is built to order with a large variety of options available, ensuring each customer gets a unit that is designed to meet their specific needs. Download Information

Minimum Power Requirements: 100 hp / 75 kW
Unit Capacity: Struck Capacity: 565 ft^3 / 16.0 m^3, Capacity with Extension: 649 ft^3 / 18.4 m^3
Tires: (2) 385x65R-22.5 Tires
Empty Weight: 12,835 lbs / 5,822 kg
Max Payload: 14,000 lbs / 6,350 kg
Dimensions: Height: 116" / 295 cm, Height w/ 10" Extension: 126" / 320 cm, Overall Width: 103" / 262 cm, Overall Length : 242" / 615 cm
Drive / rpm PTO: (2) Heavy-Duty, Two-Stage Planetary Drives / 540 or 1000 rpm PTO
Standard Discharge Ground Clearance: Flat: 28" / 71 cm, Dogleg: 41" / 104 cm, Ext. Dogleg: 52" / 132 cm, 42" Folding: 43" / 109 cm, 54" Folding: 48" / 122 cm
Number of Knives : (10) Replaceable Forage Cutting Blades
Conveyor: Front Center Door With 8’ Flat Conveyor
Floor Thickness: 3/4’’ / 19 mm M/S Floor
Wall Thickness: 1/4” / 6 mm AR200 Walls
Standards Specifications: Two Patented Freestanding Vertical Cutting Augers, Manual Restrictor Plates, Heavy-Duty Tubular Steel Frame, 5/8” / 16 mm AR200 Auger Flighting, Ultra Wear Kicker Plates, Removable Heavy Duty Hitch Jack, 4 pt Scale System, 12 Volt Battery, SS Conveyor Top Pan, Independent Steel Oil Reservoirs, Viewing Platform

Image not found or type unknown

