

## Supreme 900T Twin Auger

[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [All Equipment](#), [Supreme TMR Feed Mixer Wagons](#)

**Tags:** [mixer](#), [supreme](#)



### Product Description

[embed]https://youtu.be/Kf9-o2oAtt0?si=fhCJAVq9J90uzWmd[/embed] A Supreme Feed Processor helps you provide nutritious rations for your cattle by improved mix quality through superior tub and auger design. Along with great ROI from your feedstuffs, a Supreme Feed Processor provides a great investment as it holds high resale value. You enjoy the reliability you need from a well-built machine made with quality components. The 900T Pull-Type has a maximum payload of 24,000 lbs (10,886 kg), struck capacity of 731 ft<sup>3</sup> (20.7 m<sup>3</sup>) or 841 ft<sup>3</sup> (23.8 m<sup>3</sup>) with tub extension, and requires 130 horse power (97 kW). Unlike most other vertical mixers that use smaller single stage planetary drives, Supreme uses the heaviest two-stage planetary drive available. Combined with a heavy duty gearbox, this robust system rotates the auger through the toughest of materials. This simple design features few moving parts with no chains, sprockets or countershafts to worry about. Each Supreme pull type is built to order with a large variety of options available, ensuring each customer gets a unit that is designed to meet their specific needs. [Download Information](#)

**Minimum Power Requirements:** 130 hp / 97 kW

**Unit Capacity:** Struck Capacity: 731 ft<sup>3</sup> / 20.7 m<sup>3</sup>, Capacity with Extension: 841 ft<sup>3</sup> / 23.8 m<sup>3</sup>

**Tires:** (4) 11R/22.5in 16 Ply Truck Tires With Budd Wheels & HD Axle

**Empty Weight:** 16,259 lbs / 7,375 kg

**Max Payload:** 24,000 lbs / 10,886 kg

**Dimensions:** Height: 117" / 297 cm, Height w/ 10" Extension: 127" / 323 cm, Overall Width: 123" / 312 cm, Overall Length : 273" / 693 cm

**Drive / rpm PTO:** (2) Heavy-Duty, Two-Stage Planetary Drives / 540 or 1000 rpm PTO

**Standard Discharge Ground Clearance:** Flat: 30" / 76 cm, Dogleg: 44" / 112 cm, Ext. Dogleg: 55" / 140 cm, 42" Folding: 53" / 135 cm, 54" Folding: 60" / 152 cm

**Number of Knives :** (10) Replaceable Forage Cutting Blades

**Conveyor:** Front Center Door With 10' Flat Conveyor

**Floor Thickness:** 3/4" / 19 mm M/S Floor

**Wall Thickness:** 1/4" / 6 mm AR200 Walls

**Standards Specifications:** SS Auger Outer Edge, Two Patented Freestanding Vertical Cutting Augers, Manual Restrictor Plates, Heavy-Duty Tubular Steel Frame, 5/8" / 16 mm AR200 Auger Flighting, Ultra Wear Kicker Plates, Removable Heavy Duty Hitch Jack, 4 pt Scale System, 12 Volt Battery, Independent Steel Oil Reservoirs, SS Conveyor Top Pan

image not found or type unknown

