

Supreme 1900TR Tridem Axle Triple Auger

[Read More](#)

SKU:

Price:

Stock: instock

Categories: [All Equipment](#), [Supreme TMR Feed Mixer Wagons](#)

Tags: [mixer](#), [supreme](#)



Product Description

The 1900TR Pull-Type has a maximum payload of 60,000 lbs (27,216 kg), struck capacity of 1,674 ft³ (47.4 m³) or 1,873 ft³ (53.0 m³) with tub extension, and requires 250 horse power (186 kW). A Supreme Feed Processor helps you provide nutritious rations for your cattle by improved mix quality through superior tub and auger design. Along with great ROI from your feedstuffs, a Supreme Feed Processor provides a great investment as it holds high resale value. You enjoy the reliability you need from a well-built machine made with quality components. Coming standard with a two-speed autoshift transmission and tridem steerable axle undercarriage this processor is ready to get the job done. Unlike most other vertical mixers that use smaller single stage planetary drives, Supreme uses the heaviest two-stage planetary drive available. Combined with a heavy duty gearbox, this robust system rotates the auger through the toughest of materials. This simple design features few moving parts with no chains, sprockets or counter-shafts to worry about. Each Supreme pull type is built to order with a large variety of options available, ensuring each customer gets a unit that is designed to meet their specific needs. [Download Information](#)

Minimum Power Requirements: 250 hp / 186 kW

Unit Capacity: Struck Capacity: 1,674 ft³ / 47.4 m³, Capacity with Extension: 1,873 ft³ / 53.0 m³

Tires: 11R / 22.5in 16 Ply Truck Tires with Budd Wheels & Tridem Steerable Braking ADR Axles with Greasable ADR Hubs

Empty Weight: N/A

Max Payload: 60,000 lbs / 27,216 kg

Dimensions: Height: 150" / 381 cm, Height w/ 10" Extension: 160" / 406 cm, Overall Width: 130" / 330 cm, Overall Length : 400" / 1,016 cm

Drive / rpm PTO: (3) 2 Stage HD Planetary Drives / 1000 rpm PTO / Autoshift Transmission

Standard Discharge Ground Clearance: Flat: 41" / 104 cm, Dogleg: 55" / 140 cm, Ext. Dogleg: 66" / 168 cm, 42" Folding: 64" / 163 cm, 54" Folding: 71" / 180 cm, Side Door Chute: 35" / 89 cm

Number of Knives : (15) Replaceable Forage Cutting Blades

Conveyor: Front Center Door with 10' Flat Conveyor

Floor Thickness: 1" / 25 mm M/S Floor

Wall Thickness: 5/16" / 8 mm AR200 Walls

Standards Specifications: Three Patented Freestanding Vertical Cutting Augers, Heavy-Duty Tubular Steel Frame, 5/8" / 16 mm AR200 Auger Flighting, Ultra Wear Kicker Plates, Removable Heavy Duty Hitch Jack, 6

pt Scale System, Articulating Hitch, Stainless Steel Auger Outer Edge, Independent Steel Oil Reservoirs, Viewing Platform, Two-Speed Autoshift Transmission

Image not found or type unknown

