



3000LTR Donder Spreader

[Read More](#)

SKU:

Price:

Stock: instock

Categories: [All Equipment](#), [Donder Fertiliser Spreaders](#)

Tags: [donder](#), [fert](#), [fertiliser](#), [spreader](#), [urea](#)

Product Description

CGSA 3000 Linkage Fertiliser Spreader

A popular choice for many Australian Farmers Donder's 3000 Fertiliser Spreader is designed to spread granulated fertilisers and offer great capacity, simplicity and performance.

Width - 2930mm Height - 1830mm Length - 1300mm Weight - 572kg Capacity - 3000ltrs **Required Horsepower** Minimum: 150 hp **Spreader Capacities** Urea: 2250 kg Single Super: 3000 kg Capable of spreading as low as 2kg/ha of Slug Bait (Metarex) @ 24m wide and 14km/h or up to 325kg/ha of Urea @ 30m wide at 14km/hr ADJUSTABLE WORKING WIDTHS - Donder's stainless steel spinners are fitted with adjustable vanes, by moving the position of these vanes along the scale we can adjust the desired spread width per product to ensure an even and accurate spread pattern.

STANDARD - EASY RATE ADJUSTMENT - Rate adjustment requires no tools. Simply unlock the handle and slide the gate to the desired position. - Donder Spreaders come standard as a manual set system. This means you determine the desired rate, spread width & Speed. - Provided you maintain your speed and working width your rate will be accurate.

ACCURATE METERING AT LOW RATES - The metering orifice is designed so that the first section is able to accurately meter low rates of seed (1 – 10kg/ha) & bait whilst once past the neck of the hole the rate can be increased to allow high rates of granulated fertiliser

STAINLESS STEEL METERING UNIT - The metering system components including: + Agitator + Metering Slides + Hydraulic Slides + Spinners + Spinner Shrouds

These are all made from stainless steel to improve the longevity of these machine components and to maintain accuracy over the life of your Donder spreader

FOLDING TARP & MUDGUARDS STANDARD - Some things should just be standard. So Donder Spreaders include components such as protective tarpaulin cover and mudguards ready for whatever conditions you throw at it.

HYDRAULIC SHUTTER CONTROL - Donder Spreaders are fitted with a two-slide mechanism. One slide covers a portion of the opening to set your rate. - The Second Slide is connected to a double acting hydraulic

cylinder which is operated in cab. This allows or cuts flow of material onto the spinners
