



JBS Equipment E-Series Manure Spreader

[Read More](#)

SKU:

Price:

Stock: instock

Categories: [All Equipment](#), [JBS Equipment Manure Spreaders](#)

Product Description

Whether you run a large agricultural operation or a family farm, you'll get maximum work done quickly with this #1 best-selling spreader. Featuring the same innovative technology and quality construction as the JBS [commercial models](#), the JBS E-Series Spreader comes with an upgraded long-link floor chain, quick-attach Vertimax beaters, and steel idler sprockets. A heavy-duty yet affordable machine. The E-Series comes in a variety of sizes and can be loaded with even your smallest equipment.

- Hydraulic guillotine gate.
- Quick-attach vertical beaters.
- Low maintenance hydraulic gearbox.
- UHMW low friction hard-wearing plastic floor.
- Long-link 5/8" grade 100-floor chain.

Optional Upgrades

- [Hurricane Beaters](#) – Consistent and accurate spreading for low applications of lightweight and fine materials.
- Scale & Rate Controller System – For improved spreading accuracy.
- Flight Protection System – Add extra protection for beater knives.

[Download Information](#)

Model Number	VMEC1636SA	VMEC1648	VMEC1848	VMEC2048	VMEC2248	VMEC2448	VMEC2648
Dimensions							
Overall Length (in)	294	296	319	337	361	385	409
Overall Height (in)	118	118	118	122	122	122	122
Overall Width (in)	135	132	135	135	135	135	135
Inside Box Width (in)	78	78	78	78	78	78	78

ModelNumber	VMEC1636SA	VMEC1648	VMEC1848	VMEC2048	VMEC2248	VMEC2448	VMEC2648
Inside Box Length (in)	168	168	192	216	240	264	288
Load Height (in)	76	89	89	91	91	91	91
Level Capacity (ft ³)	317	425	475	530	580	633	686
Heaped Capacity (ft ³)	425	530	600	660	728	792	858
Carrying Capacity (lbs)	25,000	50,000	50,000	50,000	50,000	50,000	50,000
Empty Weight (lbs)	9000	10,500	12,500	14,500	16,500	18,500	21,500
Box Construction	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge
Standard Features							
Suspension	Spring	Spring	Spring	Spring	Spring	Spring	Spring
Axle	Single	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem
Tire Size	600/50-22.5	600/50-22.5	600/50-22.5	600/50-22.5	600/50-22.5	600/50-22.5	600/50-22.5
Tire Options	Yes	Yes	Yes	Yes	Yes	Yes	Yes
End Gate	Guillotine	Guillotine	Guillotine	Guillotine	Guillotine	Guillotine	Guillotine
Bulkhead	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Hitch Type	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Decal Package	Basic	Basic	Basic	Basic	Basic	Basic	Basic
Apron/Floor							
Floor Chain	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100
Galvanized & Removable Cross Slats	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Floor Drive	Single	Single	Single	Single	Dual	Dual	Dual
UHMW Plastic Floor	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Steel Idler Sprocket with Bronze Brushings	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Beaters							
Vertimax Vertical Beaters	Yes	Yes	Yes	Yes	Yes	Yes	Yes

ModelNumber	VMEC1636SA	VMEC1648	VMEC1848	VMEC2048	VMEC2248	VMEC2448	VMEC2648
Hurricane Compost Attachment	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Quick Attach Beaters	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hardox Lined Beaters	No	No	No	No	No	No	No
Mechanical Horse-power (HP) Requirements	110-150	125-150	140-175	160-200	175-225	185-220	200-275
Beater Protection	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt
Hydraulic Brakes	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Steering Axle(s)	No	No	No	No	No	No	No
Rear Drive Shaft Diameter (in)	2 3/16	2 3/16	2 3/16	2 3/16	2 3/16	2 3/16	2 3/16
Optional Upgrades							
Silage Kit	No	No	No	No	No	No	No
Wall Extensions	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Scale and Rate Controller Systems	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Flight Protection System	Optional	Optional	Optional	Optional	Optional	Optional	Optional