



JBS Equipment Low Rider Manure Spreader

[Read More](#)

SKU:

Price:

Stock: instock

Categories: [JBS Equipment Manure Spreaders](#)

Tags: [JBS](#), [manure spreader](#), [spreader](#)

Product Description

[embed]https://www.youtube.com/watch?v=0q1PcJGox_Q[/embed] The **Tandem**, **Tridem** and **Quad Axle** Low-Rider Manure Spreaders will deliver a smooth ride on even the toughest terrain. Their low center of gravity and large tires combined with the optional JBS electronic steering system to provide in-field stability that your large-scale or custom farming operation can count on. The JBS Low-Rider Spreaders are the perfect spreader for customers who know exactly what it is they need to get the job done. The newly engineered Quad Axle Low-Rider was created for large commercial farms and custom operators. Its low center gravity and large tires provide you with the stability and versatility you need while boasting a massive Quad Axle 64tonne Spring suspension! At 36' long the Quad Axle Low-Rider will allow you to spread more acres per load and get the day done faster and more efficiently.

Tandem Features

- Heaped capacity of 26 m³.
- Tough & reliable 750-60R-30.5 tires.
- 34-ton Spring Suspension.

Tridem Features

- Heaped capacity of 37 m³.
- Tough & reliable 750-60R-30.5 tires.
- 50-ton hydraulic suspension with weight transfer axle.

Quad Axle Features

- Massive heaped capacity of 46 m³.
- Tough & reliable 750-60R-30.5 tires.
- Largest, most versatile pull-type [Wide Body](#) spreader.
- 64-ton Spring Suspension.

Optional Upgrades

- Hardox® Beaters- A wear-resistant steel that extends the life of your JBS machine's beaters.
- Scale & Rate Controller System – For improved spreading accuracy.

- Flight Protection System – Add extra protection for beater knives.
- Electronic Forced Steering System – Unbeatable maneuverability and flotation with the most advanced steering system on the market.

[Download Information](#) [JBS Equipment Low Rider Manure Spreader video](#)

Model Number	VMWB2630-34L	VMWB3042-48L	VMWB3042-5
Dimensions			
Overall Length (in)	437	486	486
Overall Height (in)	143	156	153
Overall Width (in)	161	161	162
Inside Box Width (in)	82	82	82
Inside Box Length (in)	290	336	336
Load Height (in)	122	132	108
Level Capacity (ft ³)	780	1100	1100
Heaped Capacity (ft ³)	918	1260	1320
Carrying Capacity (lbs)	68,000	96,000	100,000
Empty Weight (lbs)	29,700	37,300	35,500
Box Construction	10 Gauge	10 Gauge	10 Gauge
Standard Features			
Suspensions	Spring	Spring	Hydraulic
Axle	Tandem	Tridem	Tridem
Tire Size	750-60R-30.5	750-60R-30.5	750-60R-30.5
Tire Options	No	No	No
End Gate	Guillotine	Guillotine	Guillotine
Bulkhead	Standard	Standard	Standard
Hitch Type	Equal Angle	Equal Angle	Equal Angle
Decal Package	Premium	Premium	Premium
Apron/Floor			
Floor Chain Long-Link 5/8" Grade 100	Yes	Yes	Yes
Galvanized & Removable Cross Slats	Yes	Yes	Yes
Floor Drive	Dual	Dual	Dual
UHMW Plastic Floor	Yes	Yes	Yes
Steel Idler Sprocket with Bronze Brushings	Yes	Yes	Yes
Beaters			
Vertimax Vertical Beaters	Yes	Yes	Yes
Hurricane Beaters	Optional	Optional	Optional
Quick Attach Beaters	Yes	Yes	Yes
Hardox Lined Beaters	Optional	Optional	Optional
Mechanical			
Beater Protection	Shear Bolt	Shear Bolt	Shear Bolt
Hydraulic Brakes	Yes	Yes	Yes

Model Number	VMWB2630-34L	VMWB3042-48L	VMWB3042-5
Steering Axle(s)	Yes	Yes	Yes
Rear Drive Shaft Diameter (in)	2 7/16	2 7/16	2 7/16
Add Ons			
Silage Kit	No	No	No
Wall Extensions	Included	Included	Included
Scale and Rate Controller Systems	Optional	Optional	Optional
Flight Protection System	Optional	Optional	Optional