



## 1500LTR Donder Spreader

[Read More](#)

**SKU:**

**Price:** \$11,000.00

**Stock:** instock

**Categories:** [All Equipment](#), [Donder Fertiliser Spreaders](#)

**Tags:** [donder](#), [fert](#), [fertiliser](#), [spreader](#), [urea](#)

### Product Description

## CGSA 1500 Linkage Fertiliser Spreader

The Donder 1500 Fertiliser Spreader is the smallest in the Donder Spreader Australia Range. It is designed to spread granulated fertilisers for multiple applications and tractors at an economical price. **Required Horsepower** Minimum: 90 hp **Spreader Capacities** Urea: 1125 kg Single Super: 1500 kg Capable of spreading as low as 2kg/ha of Slug Bait (Metarex) @ 24m wide and 14km/h or up to 325kg/ha of Urea @ 30m wide at 14km/hr

Width - 2140 mm Height - 1400 mm Length - 1320 mm Weight - 443 kg Capacity - 1474 ltrs ADJUSTABLE WORKING WIDTHS - Donder's stainless steel spinners are fitted with adjustable vanes, by moving the position of these vanes along the scale we can adjust the desired spread width per product to ensure an even and accurate spread pattern.

STANDARD - EASY RATE ADJUSTMENT - Rate adjustment requires no tools. Simply unlock the handle and slide the gate to the desired position. - Donder Spreaders come standard as a manual set system. This means you determine the desired rate, spread width & Speed. - Provided you maintain your speed and working width your rate will be accurate.

ACCURATE METERING AT LOW RATES - The metering orifice is designed so that the first section is able to accurately meter low rates of seed (1 – 10kg/ha) & bait whilst once past the neck of the hole the rate can be increased to allow high rates of granulated fertiliser

STAINLESS STEEL METERING UNIT - The metering system components including: + Agitator + Metering Slides + Hydraulic Slides + Spinners + Spinner Shrouds

These are all made from stainless steel to improve the longevity of these machine components and to maintain accuracy over the life of your Donder spreader

FOLDING TARP & MUDGUARDS STANDARD - Some things should just be standard. So Donder Spreaders include components such as protective tarpaulin cover and mudguards ready for whatever conditions you throw at it.

HYDRAULIC SHUTTER CONTROL - Donder Spreaders are fitted with a two-slide mechanism. One slide covers a portion of the opening to set your rate. - The Second Slide is connected to a double acting hydraulic

cylinder which is operated in cab. This allows or cuts flow of material onto the spinners



## 2500LTR Donder Spreader

[Read More](#)

**SKU:**

**Price:** \$13,000.00

**Stock:** instock

**Categories:** [All Equipment](#), [Donder Fertiliser Spreaders](#)

**Tags:** [donder](#), [fert](#), [fertiliser](#), [spreader](#), [urea](#)

### Product Description

## CGSA 2500 Linkage Fertiliser Spreader

The Donder 2500 Fertiliser Spreader is a mid capacity machine designed to spread various granulated fertilisers that strikes a balance between machine capacity and horsepower requirements **Required Horsepower** Minimum: 130 hp **Spreader Capacities** Urea: 1700 kg Single Super: 2350 kg Capable of spreading as low as 2kg/ha of Slug Bait (Metarex) @ 24m wide and 14km/h or up to 325kg/ha of Urea @ 30m wide at 14km/hr

Width - 2500 mm Height - 1600 mm Length - 1300 mm Weight - 480 kg Capacity - 2350 ltrs ADJUSTABLE WORKING WIDTHS - Donder's stainless steel spinners are fitted with adjustable vanes, by moving the position of these vanes along the scale we can adjust the desired spread width per product to ensure an even and accurate spread pattern.

STANDARD - EASY RATE ADJUSTMENT - Rate adjustment requires no tools. Simply unlock the handle and slide the gate to the desired position. - Donder Spreaders come standard as a manual set system. This means you determine the desired rate, spread width & Speed. - Provided you maintain your speed and working width your rate will be accurate.

ACCURATE METERING AT LOW RATES - The metering orifice is designed so that the first section is able to accurately meter low rates of seed (1 – 10kg/ha) & bait whilst once past the neck of the hole the rate can be increased to allow high rates of granulated fertiliser

STAINLESS STEEL METERING UNIT - The metering system components including: + Agitator + Metering Slides + Hydraulic Slides + Spinners + Spinner Shrouds

These are all made from stainless steel to improve the longevity of these machine components and to maintain accuracy over the life of your Donder spreader

FOLDING TARP & MUDGUARDS STANDARD - Some things should just be standard. So Donder Spreaders include components such as protective tarpaulin cover and mudguards ready for whatever conditions you throw at it.

HYDRAULIC SHUTTER CONTROL - Donder Spreaders are fitted with a two-slide mechanism. One slide covers a portion of the opening to set your rate. - The Second Slide is connected to a double acting hydraulic cylinder which is operated in cab. This allows or cuts flow of material onto the spinners



## 4000LTR Donder Spreader

[Read More](#)

**SKU:**

**Price:** \$16,000.00

**Stock:** instock

**Categories:** [All Equipment](#), [Donder Fertiliser Spreaders](#)

**Tags:** [donder](#), [fert](#), [fertiliser](#), [spreader](#), [urea](#)

### Product Description

## CGSA 4000 Linkage Fertiliser Spreader

The biggest seller in the Donder Fertiliser Spreader range is the 4000. Large capacity and is designed to spread more granulated fertilisers saving you plenty of time and money. **Required Horsepower** Minimum: 200 hp **Spreader Capacities** Urea: 3000 kg Single Super: 4000 kg Capable of spreading as low as 2kg/ha of Slug Bait (Metarex) @ 24m wide and 14km/h or up to 325kg/ha of Urea @ 30m wide at 14km/hr Width - 3181 mm Height - 2218 mm Length - 1496 mm Weight - 720kg Capacity - 4000ltrs ADJUSTABLE WORKING WIDTHS - Donder's stainless steel spinners are fitted with adjustable vanes, by moving the position of these vanes along the scale we can adjust the desired spread width per product to ensure an even and accurate spread pattern.

**STANDARD - EASY RATE ADJUSTMENT** - Rate adjustment requires no tools. Simply unlock the handle and slide the gate to the desired position. - Donder Spreaders come standard as a manual set system. This means you determine the desired rate, spread width & Speed. - Provided you maintain your speed and working width your rate will be accurate.

**ACCURATE METERING AT LOW RATES** - The metering orifice is designed so that the first section is able to accurately meter low rates of seed (1 – 10kg/ha) & bait whilst once past the neck of the hole the rate can be increased to allow high rates of granulated fertiliser

**STAINLESS STEEL METERING UNIT** - The metering system components including: + Agitator + Metering Slides + Hydraulic Slides + Spinners + Spinner Shrouds

These are all made from stainless steel to improve the longevity of these machine components and to maintain accuracy over the life of your Donder spreader

**FOLDING TARP & MUDGUARDS STANDARD** - Some things should just be standard. So Donder Spreaders include components such as protective tarpaulin cover and mudguards ready for whatever conditions you

throw at it.

HYDRAULIC SHUTTER CONTROL - Donder Spreaders are fitted with a two-slide mechanism. One slide covers a portion of the opening to set your rate. - The Second Slide is connected to a double acting hydraulic cylinder which is operated in cab. This allows or cuts flow of material onto the spinners

---



## 3000LTR Donder Spreader

[Read More](#)

**SKU:**

**Price:** \$14,000.00

**Stock:** instock

**Categories:** [All Equipment](#), [Donder Fertiliser Spreaders](#)

**Tags:** [donder](#), [fert](#), [fertiliser](#), [spreader](#), [urea](#)

### Product Description

## CGSA 3000 Linkage Fertiliser Spreader

A popular choice for many Australian Farmers Donder's 3000 Fertiliser Spreader is designed to spread granulated fertilisers and offer great capacity, simplicity and performance.

Width - 2930mm Height - 1830mm Length - 1300mm Weight - 572kg Capacity - 3000ltrs **Required Horsepower** Minimum: 150 hp **Spreader Capacities** Urea: 2250 kg Single Super: 3000 kg Capable of spreading as low as 2kg/ha of Slug Bait (Metarex) @ 24m wide and 14km/h or up to 325kg/ha of Urea @ 30m wide at 14km/hr **ADJUSTABLE WORKING WIDTHS** - Donder's stainless steel spinners are fitted with adjustable vanes, by moving the position of these vanes along the scale we can adjust the desired spread width per product to ensure an even and accurate spread pattern.

**STANDARD - EASY RATE ADJUSTMENT** - Rate adjustment requires no tools. Simply unlock the handle and slide the gate to the desired position. - Donder Spreaders come standard as a manual set system. This means you determine the desired rate, spread width & Speed. - Provided you maintain your speed and working width your rate will be accurate.

**ACCURATE METERING AT LOW RATES** - The metering orifice is designed so that the first section is able to accurately meter low rates of seed (1 – 10kg/ha) & bait whilst once past the neck of the hole the rate can be increased to allow high rates of granulated fertiliser

**STAINLESS STEEL METERING UNIT** - The metering system components including: + Agitator + Metering Slides + Hydraulic Slides + Spinners + Spinner Shrouds

These are all made from stainless steel to improve the longevity of these machine components and to maintain accuracy over the life of your Donder spreader

**FOLDING TARP & MUDGUARDS STANDARD** - Some things should just be standard. So Donder Spreaders include components such as protective tarpaulin cover and mudguards ready for whatever conditions you throw at it.

**HYDRAULIC SHUTTER CONTROL** - Donder Spreaders are fitted with a two-slide mechanism. One slide covers a portion of the opening to set your rate. - The Second Slide is connected to a double acting hydraulic cylinder which is operated in cab. This allows or cuts flow of material onto the spinners

---