

JBS Equipment M-Series Spreader

Read More SKU: Price: Stock: instock Categories: <u>All Equipment</u>, <u>JBS Equipment Manure</u> <u>Spreaders</u> Tags: JBS, m-series, manure, manure spreader, spreader

Product Description

Versatile. Accessible. Maneuverable. Reliable. The M-Series is about to become the new industry standard for compact manure spreaders. If you're a growing farm that's ready to take the next step in spreading, a lower-acreage farm that's short on storage space, or a large operation that wants versatility, the M-Series may be right for you. Featuring a compact design and low load height, the JBS Mini spreader offers maximum portability, making it perfect for small to medium-sized farm operations. Engineered to be ultra-efficient, it runs with less horsepower than our E-Series and has a uni-body design that allows it to be shipped in many different ways.

- Hydraulic guillotine gate.
- Low horsepower tractor operation 90-130HP.
- UHMW low friction hard-wearing plastic floor.
- 3/8? Grade 100 floor chain.

Download Information Video of JBS Equipment M-Series Manure Spreader



JBS Equipment Low Rider Manure Spreader

Read More

SKU: Price: Stock: instock Categories: <u>JBS Equipment Manure Spreaders</u> Tags: JBS, manure spreader, spreader

Product Description

[embed]https://www.youtube.com/watch?v=0q1PcJGox_Q[/embed] The **Tandem, Tridem** and **Quad Axle** Low-Rider Manure Spreaders will deliver a smooth ride on even the toughest terrain. Their low center of gravity and large tires combined with the optional JBS electronic steering system to provide in-field stability that your large-scale or custom farming operation can count on. The JBS Low-Rider Spreaders are the perfect spreader for customers who know exactly what it is they need to get the job done. The newly engineered Quad Axle Low-Rider was created for large commercial farms and custom operators. Its low center gravity and large tires provide you with the stability and versatility you need while boasting a massive Quad Axle 64tonne Spring suspension! At 36' long the Quad Axle Low-Rider will allow you to spread more acres per load and get the day done faster and more efficiently.

Tandem Features

- Heaped capacity of 26 m³.
- Tough & reliable 750-60R-30.5 tires.
- 34-ton Spring Suspension.

Tridem Features

- Heaped capacity of 37 m³.
- Tough & reliable 750-60R-30.5 tires.
- 50-ton hydraulic suspension with weight transfer axle.

Quad Axle Features

- Massive heaped capacity of 46 m³.
- Tough & reliable 750-60R-30.5 tires.
- Largest, most versatile pull-type Wide Body spreader.
- 64-ton Spring Suspension.

Optional Upgrades

- Hardox® Beaters- A wear-resistant steel that extends the life of your JBS machine's beaters.
- Scale & Rate Controller System For improved spreading accuracy.
- Flight Protection System Add extra protection for beater knives.
- Electronic Forced Steering System Unbeatable maneuverability and flotation with the most advanced steering system on the market.

Download Information JBS Equipment Low Rider Manure Spreader video

Model Number	VMWB2630-34L	VMWB3042-48L	VMWB3042-5	
Dimensions				
Overall Length (in)	437	486	486	
Overall Height (in)	143	156	153	
Overall Width (in)	161	161	162	
Inside Box Width (in)	82	82	82	
Inside Box Length (in)	290	336	336	
Load Height (in)	122	132	108	
Level Capacity (ft ³)	780	1100	1100	
Heaped Capacity (ft ³)	918	1260	1320	
Carrying Capacity (lbs)	68,000	96,000	100,000	
Empty Weight (lbs)	29,700	37,300	35,500	
Box Construction	10 Gauge	10 Gauge	10 Gauge	
Standard Features				

VMWB2630-34L	VMWB3042-48L	VMWB3042-5
Spring	Spring	Hydraulic
Tandem	Tridem	Tridem
750-60R-30.5	750-60R-30.5	750-60R-30.5
No	No	No
Guillotine	Guillotine	Guillotine
Standard	Standard	Standard
Equal Angle	Equal Angle	Equal Angle
Premium	Premium	Premium
Yes	Yes	Yes
Yes	Yes	Yes
Dual	Dual	Dual
Yes	Yes	Yes
Yes	Yes	Yes
Yes	Yes	Yes
Optional	Optional	Optional
Yes	Yes	Yes
Optional	Optional	Optional
Shear Bolt	Shear Bolt	Shear Bolt
Yes	Yes	Yes
Yes	Yes	Yes
2 7/16	2 7/16	2 7/16
No	No	No
Included	Included	Included
Optional	Optional	Optional
Optional	Optional	Optional
	Spring Tandem 750-60R-30.5 No Guillotine Standard Equal Angle Premium Yes Dual Yes Dual Yes Yes Optional Yes Optional Yes Optional Shear Bolt Yes 2 7/16 No Included Optional	Spring TandemSpring Tridem750-60R-30.5750-60R-30.5NoNoGuillotineGuillotineStandardStandardEqual Angle PremiumEqual Angle PremiumYes



JBS Equipme Spreader

Read More SKU: Price: Stock: instock

Categories: <u>All Equipment</u>, <u>JBS Equipment Manure</u> Spreaders

Product Description

Whether you run a large agricultural operation or a family farm, you'll get maximum work done quickly with this #1 best-selling spreader. Featuring the same innovative technology and quality construction as the JBS commercial models, the JBS E-Series Spreader comes with an upgraded long-link floor chain, quick-attach Vertimax beaters, and steel idler sprockets. A heavy-duty yet affordable machine. The E-Series comes in a variety of sizes and can be loaded with even your smallest equipment.

- Hydraulic guillotine gate.
- Quick-attach vertical beaters.
- Low maintenance hydraulic gearbox.
- UHMW low friction hard-wearing plastic floor.
- Long-link 5/8? grade 100-floor chain.

Optional Upgrades

- <u>Hurricane Beaters</u> Consistent and accurate spreading for low applications of lightweight and fine materials.
- Scale & Rate Controller System For improved spreading accuracy.
- Flight Protection System Add extra protection for beater knives.

Model Number	VMEC1636SA	VMEC1648	VMEC1848	VMEC2048	VMEC2248	VMEC2448	VMEC2648
Dimensions							
Overall Length (in)	294	296	319	337	361	385	409
Overall Height (in)	118	118	118	122	122	122	122
Overall Width (in)	135	132	135	135	135	135	135
Inside Box Width (in)	78	78	78	78	78	78	78
Inside Box Length (in)	168	168	192	216	240	264	288
Load Height (in)	76	89	89	91	91	91	91
Level Capacity (ft ³)	317	425	475	530	580	633	686
Heaped Capacity (ft ³)	425	530	600	660	728	792	858
Carrying Capacity (lbs)	25,000	50,000	50,000	50,000	50,000	50,000	50,000

ModelNumber	VMEC1636SA	VMEC1648	VMEC1848	VMEC2048	VMEC2248	VMEC2448	VMEC2648
Empty Weight (lbs)	9000	10,500	12,500	14,500	16,500	18,500	21,500
Box Construction Standard Features	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge
Suspension	Spring	Spring	Spring	Spring	Spring	Spring	Spring
Axle	Single	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem
Tire Size	600/50-22.5	600/50-22.5	600/50-22.5	600/50-22.5	600/50-22.5	600/50-22.5	600/50-22.5
Tire Options	Yes	Yes	Yes	Yes	Yes	Yes	Yes
End Gate	Guillotine	Guillotine	Guillotine	Guillotine	Guillotine	Guillotine	Guillotine
Bulkhead	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Hitch Type	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Decal Package		Basic	Basic	Basic	Basic	Basic	Basic
Apron/Floor	Duolo	20010	Daoio	Daoio	Duolo	Daoio	Duolo
Floor Chain	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100					
Galvanized &							
Removable Cross Slats	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Floor Drive	Single	Single	Single	Single	Dual	Dual	Dual
UHMW Plastic Floor	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Steel Idler Sprocket with Bronze Brushings	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Beaters							
Vertimax Vertical Beaters	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hurricane Compost Attachment	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Quick Attach Beaters	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hardox Lined Beaters	No	No	No	No	No	No	No
Mechanical							

	VMEC1636SA	VMEC1648	VMEC1848	VMEC2048	VMEC2248	VMEC2448	VMEC2648
Horse-power (HP) Requirements	110-150	125-150	140-175	160-200	175-225	185-220	200-275
Beater Protection	Shear Bolt						
Hydraulic Brakes	Optional						
Steering Axle(s)	No						
Rear Drive Shaft Diameter (in)	2 3/16	2 3/16	2 3/16	2 3/16	2 3/16	2 3/16	2 3/16
Optional Upgrades							
Silage Kit	No						
Wall Extensions	Optional						
Scale and Rate Controller Systems	Optional						
Flight Protection System	Optional						