

## Supreme 600T Twin Auger

[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Supreme TMR Feed Mixer Wagons](#), [All Equipment](#)

**Tags:** [mixer](#), [supreme](#)



### Product Description

[embed]https://youtu.be/k\_kjO8uC9sw?si=4ZI9KVJANXZpOncO[/embed] A Supreme Feed Processor helps you provide nutritious rations for your cattle by improved mix quality through superior tub and auger design. Along with great ROI from your feedstuffs, a Supreme Feed Processor provides a great investment as it holds high resale value. You enjoy the reliability you need from a well-built machine made with quality components. The 600T Pull-Type has a maximum payload of 14,000 lbs (6,350 kg), struck capacity of 543 ft<sup>3</sup> (15.4 m<sup>3</sup>) or 635 ft<sup>3</sup> (18.0 m<sup>3</sup>) with tub extension, and requires 100 horse power (75 kW). Unlike most other vertical mixers that use smaller single stage planetary drives, Supreme uses the heaviest two-stage planetary drive available. Combined with a heavy duty gearbox, this robust system rotates the auger through the toughest of materials. This simple design features few moving parts with no chains, sprockets or countershafts to worry about. Each Supreme pull type is built to order with a large variety of options available, ensuring each customer gets a unit that is designed to meet their specific needs.

**Minimum Power Requirements:** 100 hp / 75 kW

**Unit Capacity: Struck Capacity:** 543 ft<sup>3</sup> / 15.4 m<sup>3</sup>, Capacity with Extension: 635 ft<sup>3</sup> / 18.0 m<sup>3</sup>

**Tires:** 385x65-22.5 Tires

**Empty Weight:** 12,730 lbs / 5,774 kg

**Max Payload:** 14,000 lbs / 6,350 kg

**Dimensions: Height:** 107" / 272 cm, Height w/ 10" Extension: 117" / 297 cm, Overall Width: 102" / 259 cm, Overall Length : 254" / 645 cm

**Drive / rpm PTO:** (2) Heavy-Duty, Two-Stage Planetary Drives / 540 or 1000 rpm PTO

**Standard Discharge Ground Clearance:** Flat: 28" / 71 cm, Dogleg: 41" / 104 cm, Ext. Dogleg: 52" / 132 cm, 42" Folding: 43" / 109 cm, 54" Folding: 48" / 122 cm

**Number of Knives :** 10 Replaceable Forage Cutting Blades

**Conveyor:** Front Center Door With 8' Flat Conveyor

**Floor Thickness:** 3/4" (19 mm) M/S Floor

**Wall Thickness:** 1/4" (6 mm) AR200 Walls

**Standards Specifications:** Patented Freestanding Vertical Mixing Auger, Manual Restrictor Plates, Heavy-Duty Tubular Steel Frame, 5/8" / 16 mm AR200 Auger Flighting, 4 pt Scale System, 12 Volt Battery, Ultra Wear Kickerplate, SS Conveyor Top Pan, Independent Steel Oil Reservoirs, Viewing Platform

