

Supreme 1200T Tandem Axle, Twin Auger



[Read More](#)

SKU:

Price:

Stock: instock

Categories: [Supreme TMR Feed Mixer Wagons](#), [All Equipment](#)

Tags: [mixer](#), [supreme](#)

Product Description

[embed]https://youtu.be/k_kjO8uC9sw?si=lvPLGQ_io3QhzbV[/embed] A Supreme Feed Processor helps you provide nutritious rations for your cattle by improved mix quality through superior tub and auger design. Along with great ROI from your feedstuffs, a Supreme Feed Processor provides a great investment as it holds high resale value. You enjoy the reliability you need from a well-built machine made with quality components. The 1200T Pull-Type has a maximum payload of 40,000 lbs (18,144 kg), struck capacity of 935 ft³ (26.5 m³) or 1,075 ft³ (30.4 m³) with tub extension, and requires 180 horse power (134 kW). Unlike most other vertical mixers that use smaller single stage planetary drives, Supreme uses the heaviest two-stage planetary drive available. Combined with a heavy duty gearbox, this robust system rotates the auger through the toughest of materials. This simple design features few moving parts with no chains, sprockets or counter-shafts to worry about. Each Supreme pull type is built to order with a large variety of options available, ensuring each customer gets a unit that is designed to meet their specific needs.

Minimum Power Requirements: 180 hp / 134 kW

Unit Capacity: Struck Capacity: 935 ft³ / 26.5 m³ Capacity with Extension: 1,075 ft³ / 30.4 m³

Tires: 275 / 70R 22.5 Truck Tires with Budd Wheels and HD Axle

Empty Weight: 23,049 lbs / 10,454 kg

Max Payload: 40,000 lbs / 18,144 kg

Dimensions: Height: 121" / 307 cm Height w/ 10" Extension: 131" / 333 cm Overall Width: 121" / 307 cm Overall Length : 319" / 810 cm

Drive / rpm PTO: Two Heavy-Duty, Two-Stage Planetary Drives / 540 or 1000 rpm PTO

Standard Discharge Ground Clearance: Flat: 37" / 94 cm Dogleg: 50" / 127 cm Ext. Dogleg: 62" / 157 cm 42" Folding: 60" / 152 cm 54" Folding: 67" / 170 cm Side Door Fixed Chute; 28" / 71 cm

Number of Knives : 10 Replaceable Forage Cutting Blades

Conveyor: Front Center Door With 10' Flat Conveyor

Floor Thickness: 1" (25 mm) M/S Floor

Wall Thickness: 1/4" (6 mm) AR200 Walls

Standards Specifications: Tandem Axle Two Patented Freestanding Vertical Mixing Auger Manual Restrictor Plates Heavy-Duty Tubular Steel Frame 5/8" / 16 mm AR200 Auger Flighting Ultra Wear Kicker Plates Removable Heavy Duty Hitch Jack 4pt Scale System 12 Volt Battery SS Conveyor Top Pan Independent Steel Oil Reservoirs Viewing Platform

image not found or type unknown

